



1.1.2 · Tabletop Auto Bagger

YPX-BD60C

Drop-Style Tabletop Auto Bagger with Print & Apply & PC

“Batch-less order fulfillment — integrated print, apply & PC control”

SPEED

**Up to 1,200 bags/
hr**

BAG SIZE

**8"-24" W × 12"-
32" L**

FILM THICKNESS

1-4 mil

WEIGHT

508 lbs (230 kg)

OVERVIEW

The YPX-BD60C upgrades the tabletop bagging platform into a complete order-fulfillment station by pairing the all-electric drop-style bagger with an integrated label print-and-apply unit and PC-based control. It keeps the air-free, plug-anywhere design of the XB40 but is sized for larger bags and higher-volume runs.



45° VIEW

DESCRIPTION

The YPX-BD60C upgrades the tabletop bagging platform into a complete order-fulfillment station by pairing the all-electric drop-style bagger with an integrated label print-and-apply unit and PC-based control. It keeps the air-free, plug-anywhere design of the XB40 but is sized for larger bags and higher-volume runs.

The BD60C runs both poly tubing and pre-opened bags on a roll. Tubing lets operators right-size bag length on the fly, cutting material cost and reducing dimensional-weight shipping charges compared with fixed pre-made bags.

An available thermal-transfer printer applies text, barcodes, or graphics directly to the film, or the print-and-apply label unit can place a shipping label at the point of packaging — producing a batch-less, ship-ready bag in a single pass.

Like the rest of the drop-style bagger line, the BD60C uses a zero-force closing seal bar, seal-flattener fingers, and an ISO 9001-aligned frame, and is built from off-the-shelf components for straightforward field service.

KEY BENEFITS

Operating Benefits

- Hand switch, manual, or full auto cycle operation
- Seal-flattener fingers minimize seal wrinkling
- Integrated print & apply label station, or optional thermal-transfer bag printing
- Compact footprint for a fulfillment work cell
- Color touchscreen interface

Set-Up Benefits

- Runs poly tubing or pre-opened bags on a roll for fast changeovers
- PLC job storage, batch counters, packaging statistics, login levels
- Ready interface for infeed devices and line automation
- Ceramic heating element for fast start-up

Maintenance Benefits

- Off-the-shelf modular components
- Remote networking for troubleshooting
- Built-in self-diagnostics
- Quick-access side covers

Safety Benefits

- Zero-force seal bar closing
- Optional light curtain interlock
- ISO 9001-aligned design

TECHNICAL DATA

Model	Drop-Style Auto Bagger — Print & Apply & PC
Speed	Up to 1,200 bags/hour
Bag Width	8" – 24"
Bag Length	12" – 32"
Bag Thickness	1 – 4 mil
Seal Width	1/8"
Power	1,200 W
Electrical	220V, 50/60Hz
Dimensions (W x D x H)	62" x 34" x 65"
Weight	508 lbs (230 kg)

Runs poly tubing or pre-opened bags on a roll; thermal-transfer printer available.

Interested in the YPX-BD60C?

Contact YXPXPACK for pricing, lead times, and a live demo.

sales@ypxpack.com
ypxpack.com
Guangzhou, Guangdong, China