



1.1.1 · Tabletop Auto Bagger

YPX-XB40

Drop-Style Tabletop Auto Bagger with Apply

"All-electric tabletop bagging — small footprint, no compressed air"

SPEED

**Up to 1,800 bags/
hr**

BAG SIZE

**3"-15" W × 6"-32"
L**

FILM THICKNESS

1-4 mil

WEIGHT

188 lbs (85 kg)

OVERVIEW

The YPX-XB40 is a fully electric tabletop bagging machine designed for e-commerce fulfillment operations that need a compact, plug-and-play solution. Because it runs entirely on standard electrical power, it eliminates the need for a compressed-air line, so it can be installed anywhere a normal outlet is available and relocated as production needs change.



45° VIEW

DESCRIPTION

The YPX-XB40 is a fully electric tabletop bagging machine designed for e-commerce fulfillment operations that need a compact, plug-and-play solution. Because it runs entirely on standard electrical power, it eliminates the need for a compressed-air line, so it can be installed anywhere a normal outlet is available and relocated as production needs change.

Weighing just over 188 lbs (85 kg) with a footprint of only 50" x 40", the XB40 loads pre-opened bags from the front of the machine, keeping the rear clear so operators never need to access the back during normal operation. It can be triggered with a hand switch, an optional touch sensor, or run continuously in automatic cycle mode.

A seal-flattener feature stretches the bag tight immediately before sealing to reduce wrinkles in the finished seal, and an optional in-line label applicator can place labels up to 4" wide directly onto the next bag in the sequence.

Built to an ISO 9001-aligned design standard with a zero-force closing seal bar, the XB40 suits e-commerce order fulfillment, kitting, light industrial, and general parts packaging where bag sizes and product mix change frequently.

KEY BENEFITS

Operating Benefits

- Cycle by hand switch, optional touch sensor, or full auto mode
- Seal-flattener fingers stretch film taut before sealing for a cleaner seal
- Optional label application up to 4" wide on the next bag out
- Compact footprint suited to tight packaging cells
- Color touchscreen with clear operator prompts

Set-Up Benefits

- Pre-opened bags-on-a-roll for fast size changeovers
- PLC job storage with batch counters and login levels
- Interface ready for infeed devices and upstream automation
- Ceramic heating element for fast warm-up

Maintenance Benefits

- Off-the-shelf modular components simplify replacement
- Remote networking support for troubleshooting
- Built-in self-diagnostics
- Quick-release side covers for fast access to electricals

Safety Benefits

- Zero-force seal bar closing minimizes pinch-point risk
- Low 800 W power draw
- Optional light curtain halts the cycle when the field is obstructed
- ISO 9001-aligned design

TECHNICAL DATA

Model	Drop-Style Auto Bagger
Speed	Up to 1,800 bags/hour
Bag Width	3" – 15"
Bag Length	6" – 32"
Bag Thickness	1 – 4 mil
Seal Width	1/8"
Power	800 W
Electrical	220V, 50/60Hz
Dimensions (W x D x H)	50" x 40" x 31"
Weight	188 lbs (85 kg)

Optional accessory: in-line label applicator (bag width up to 4").

Interested in the YPX-XB40?

Contact YPXPACK for pricing, lead times, and a live demo.

sales@ypxpack.com
ypxpack.com
Guangzhou, Guangdong, China